



LAMBERT

product data

LAMBERT SOUTHWEST

PO BOX 1111
HENDERSON, TX 75653

Introduction:

DECO-ETCH STAIN is chemically reactive acidic stain for coloring old or new concrete. This product is only effective on surfaces that contain cementitious material. **DECO-ETCH STAIN** chemically reacts with cement, it is not a paint. Surface must contain enough cementitious material for the necessary color reaction. Color reactions will vary with each surface, as cementitious content varies. Due to these variances, exact color results cannot be guaranteed. With adequate cement content, **DECO-ETCH STAIN** does produce beautiful mottled or marbled colors.

Composition:

DECO-ETCH STAIN is an acid based chemical stain. It is formulated to react with cementitious materials and produce beautiful, permanent, mottled colors. **DECO-ETCH STAIN** is available in 6 colors: Sea Mist Green, Redwood, Charcoal, Aqua Blue, Amber, and Sienna Brown. These colors will not chip, fade or peel off like paints because the stain has reacted and changed the chemical composition of the cementitious material. Due to differences in cements, colors will vary from surface to surface. Because this is an acid - based stain, it is a hazardous and corrosive material. **DECO-ETCH STAIN** should be handled with proper personal protective equipment and label instructions should be followed exactly. For more information refer to the **DECO-ETCH STAIN** Material Safety Data Sheet.

DECO-ETCH STAIN



Packaging and Shipping:

DECO-ETCH STAINS are bottled in one gallon jugs. Our stains are also available in cases which contain 4-1 gallon jugs. Because **DECO-ETCH STAIN** is a hazardous material, it must be shipped motor freight and classified accordingly. Shipping costs will vary based on quantity and final destination. Approximate shipping weights are: 1 gallon 10 lbs, 4 - 1 gallon case 40 lbs.

Availability and Cost:

DECO-ETCH STAIN is readily available from distributors throughout the South Central United States. Our distributors are backed by our reliable factory service which usually ship out orders within 24 hours. Lambert Southwest also has sales representatives who

travel our same distribution area. For the names of local distributors, sales representatives, samples, or technical information contact Lambert Southwest at 1-800-256-8655. Retail costs of **DECO-ETCH STAIN** are established by our distributors. Color Cards which show representations and product information about **DECO-ETCH STAIN** are also available from our distributors, sales representatives or our home office.

Limited Warranty:

Neither seller nor manufacturer has any knowledge or control concerning the purchaser's use of this product and no warranty is made as to the results of any use. The only obligation of either seller or manufacturer shall be to replace any quantity of this product which is proved to be defective. Any claim of defective product must be received in writing within 90 days from the date of purchase. Neither seller nor manufacturer assumes any liability for injury, loss, or damage resulting from use of this product.

For optimum results follow up the **DECO-ETCH STAIN** with **DECO-SEAL** water based sealer and a maintenance coating of **DECO-FINISH**.

For application instructions see our **DECO-ETCH STAIN** color chart.

LAMBERT SOUTHWEST
PO BOX 1111 / 1110 NORTH FRISCO
HENDERSON, TX 75653
(800)-256-8655 or (903)657-4680
Fax (903)657-4805 www.LambertSW.com
www.deco-etch.com
Lambert Southwest is a division of
GW Holladay Interests Inc.

CONCRETE - DECORATIVE - ACID STAIN

Suggested Short Form Specification for concrete: All concrete flatwork designated to be acid stained in the specifications or plans shall be stained with **DECO-ETCH STAIN**, _____ color, a chemically reactive acidic stain for coloring old or new concrete manufactured by Lambert Southwest, Henderson, TX 75653. Phone 1-800-256-8655 Fax (903)657-4805. The concrete shall be at least 14 days old, penetrable by water, clean, dry, and free of sealers, curing agents, waxes, oils, grease, or paints. Sample in an inconspicuous area should be applied at job site for approval. A minimum of two coats of **DECO-ETCH STAIN** shall be applied as described on Lambert's **DECO-ETCH STAIN** color card.